



GRENLI/TEXTURED

DESCRIPTION: Acrylic copolymer emulsion binder based, ready for application, grained exterior coating.

CHARACTERISTIC: -Long-lasting, environmental friendly. -Several decorative patterns can be obtained . -High covering ability, also closes plaster faults on the surface. -Easily applicable, water-based structure. -Minimum consumption. -Flexible, matt outward looking.

APPLICATION SURFACES: Can be applied on concrete , concrete plate , cement-based , convantional plaster and similar surfaces.

TECHNICAL INFORMATION:

Structure: Stirene acrylic

Consumption: 900- 1200 g/m²

Thinner: Water

Thinning Ratio: No thinning, ready-to-use.

Density: 1,76 ± 0,2 (g / ml)

Drying: Touch dry: after 6 hours; Hard dry: after 24 hours

Viscosity: 160 KU ± 5 (23 ° C)

PH (25°C): 8 – 9

APPLICATION TOOLS: Can be applied with roller or spray. While the material is wet, the pattern is given by posteri, coral, sponge, roller according to the desired texture.

APPLICATION: The application surface should be free from all kinds of dust, rust, dirt, oil and old paint residues. A clean, dry and solid surface should be obtained by scraping the swollen, loosened and poured painted surfaces and applying Spring Exterior Primer after the surface cracks have been leveled with Spring Putty and smoothed. The paint should be mixed until it is completely homogenous before use. Before being thinned, it is spread with equal thickness to the surface with the roller. Then, according to the texture desired to be obtained when the material is wet (pestle, coral, sponge), the pattern is given by roll. For spray



application, dilute with 8% water. Ambient and surface temperature should be between + 5°C and + 35°C during application and product drying. Care should be taken to use the same production code and dated materials in order to avoid toner discrepancies.

CAUTION: -Avoid getting eye and skin contact. In case wash with plenty of water. -Preserve in a tightly closed container. -Keep above the reach of children -Do not dump into sewer system.

STORAGE: Keep at a cool and clean place away from sun light. It can be stored unopened 1 year at room temperature.

PACKAGING: 25 Kg PE Bucket