



SPRING CONCRETE PRIMER

Definition: It is a pure acrylic based primer used to increase the adherence of the paint, plaster and other products to be made on the gross concrete.

Technical Data:

Structure: Pure Acrylic, filled, transparent primer.

Thinning ratio: Ready to use.

Consumption: 6-10 (m² / lt), 160-200 (g / m²)

Drying Time: 20 degrees and 50% relative humidity, 1 hour to initial drying, 24 hours to full drying

Application:

The application surface should be free from all kinds of dust, dirt and oil. The blistered and old painted surfaces are scraped and the defects and cracks on the surface are filled with Spring Acrylic exterior paste and smoothed and a clean, dry and solid surface is obtained. Spring Concrete Primer is applied directly by brush, roller or spray method in one coat. It should not be applied in very windy weather and under direct sunlight. Before applying the topcoat application, it should be waited at least 24 hours depending on air temperature and moisture.

Warning:

S2: Keep out of the reach of children.

S24 / 25: Avoid contact with eyes and skin.

S46: If swallowed, seek medical advice immediately; Show the container or label.

Store the product in a tightly closed container.

Do not pour into the sewer.

Storage:

It can be stored for 1 year at room temperature.

Package:

15 kg, 12 kg 6 kg 4 kg PE bucket.