



SPRING EXTERIOR PAINT

DESCRIPTION: Pure Acrylic binder based, matt appearance, water based, first class, final coat exterior paint.

CHARACTERISTIC: Acrylic paint is resistant to UV rays thanks to pigments in its structure. In addition to having high closure power, the colors retain their vitality for many years. The water-based structure does not harm human health or the environment.

APPLICATION SURFACES: Can be applied on a wide range of interior old painted surfaces such as concrete, plaster, black plaster, betopan, glass textured and paintable wallpaper.

TECHNICAL INFORMATION:

Structure: Pure acrylic

Consumption: Single coat : 6-10 m²/ lt, 100-170 (g/m²).

Thinner: Water

Thinning Ratio: %10- 15

Density: 1,58 ± 0,02 gr / ml

Drying: Touch dry: after 15-20 minutes, Dust repulsive: after 1 hour, Hard dry: after 24 hours

Viscosity: 115 KU ± 10 (23 ° C)

pH: 8 – 9

APPLICATION: The application surface should be free from all kinds of dust, dirt and oil. Once the blistered and old painted surfaces have been lightly smoothed, the application of primer should be carried out to obtain a clean, dry and solid surface. If necessary, defects and cracks on the surface should be repaired with Spring Acrylic Putty. Spring Primer on new painted and absorbent surfaces, Spring Acrylic Primer on old painted, dirty or synthetic painted surfaces. Spring Acrylic Paint is thinned with 10-15% clean water then applied in 2 layers by roller, brush or spraying method. Wait at least 2 hours between coats depending on the air temperature. Tools should be cleaned immediately after application. For new coated surfaces, at least 28 days must be waited for the application of paint to the surface. The paint should be mixed until it is completely homogenous before use. Ambient and surface temperature should be between + 5°C and + 35°C during application and product drying. If applied on very bright and glassy surfaces, a solid surface should be formed by smoothing the surface first to ensure better adhesion.



CAUTION: -Avoid getting eye and skin contact. In case wash with plenty of water. -Preserve in a tightly closed container. -Keep above the reach of children -Do not dump into sewer system.

STORAGE: Keep at a cool and clean place away from sun light. It can be stored unopened 1 year at room temperature.

PACKAGING: 20 kg ,10 kg PE Bucket