



Luminex

Product Description

Luminex is a next-generation, water-based, pure acrylic transformation paint with excellent adhesion properties on all surfaces.

Features

It has very high covering power. It provides excellent water resistance and ensures waterproofing on the applied surface. It has high chemical resistance (soap, cleaning detergents, diluted bleach, etc.). Thanks to its excellent spreading ability, it does not leave roller or brush marks and allows sufficient working time for corrections. The glossy finish obtained after application eliminates the need for additional varnish. It has strong adhesion and does not require any primer. It is resistant to dirt and stains and can be easily cleaned with a wet and soapy cloth. It has no disturbing odor. Suitable for both interior and exterior use.

Application Areas

It can be applied to all types of surfaces such as wood, furniture, parquet, laminate, ceramic, porcelain, tiles, marble, glass, plastic, metal, aluminum, galvanized surfaces, zinc, stone, walls, and wallpaper.

Thinning (by volume)

Ready to use. Stir well before application.

Drying Time (20°C)

Touch dry: 1–2 hours

Full drying: 24 hours

Applied surfaces should not be used for 1 day; surfaces exposed to water should not be used for 2 days. During the first 7 days, surfaces should be protected from standing water and impacts.

Coverage Area

1 liter can cover approximately 8–10 m² in two coats depending on the application method and surface.

Application

The surface to be painted must be clean. Remove dust, dirt, grease, silicone, and any substances that may reduce adhesion. Sanding should be done if necessary. No primer is required before application. To prevent corrosion, it is recommended to prime metal surfaces with **Luminex Anti-Rust**. After opening the package, stir Luminex until a homogeneous consistency is achieved. Apply the product without dilution onto the prepared surface using a silk brush, velvet roller, or spray system in two coats. Wait at least 2 hours between coats. During application, ensure that the surface and ambient temperature remain between +5°C and +30°C.

Warning

S2: Keep out of reach of children.

S24/25: Avoid contact with eyes and skin.

S46: If swallowed, seek medical advice immediately and show the container or label. Keep the product tightly closed. Do not pour into drains.



Storage

2 years in the original unopened packaging at room temperature.

Packaging

1 L, 0.5 L, 0.25 L plastic containers.