



SPRING ACRYLIC PUTTY

DESCRIPTION: Acrylic copolymer resin-based exterior surface correction putty.

CHARACTERISTIC:

- Healthy and environmental friendly.
- Easily applicable ,ready to-use.
- Water resistant.
- Provides smooth and durable surface.
- Provides durable surface covering all cracks and leveling roughness for topcoat application.

APPLICATION SURFACES:

Can be applied on a wide range of surfaces such as conventional plaster ,concrete , gross concrete and similar surfaces.

TECHNICAL INFORMATION

Consumption: Single coat: 0,5 – 1 (m² / kg)

Thinner: No thinning. Ready to-use

Drying: Touch dry: after 15-20 minutes, Dust repulsive: after 1 hour, Hard dry: after 24 hours

pH: 8- 9

SURFACE PREPARATION:

- The surface should be free from all kind of dust . Loose and old paintings should be scraped and surface should be dry.
- After recommended cleaning is completed , Spring Acrylic Exterior Putty can be applied.

APPLICATION:

- Spring Exterior Acrylic Putty can be applied without thinning in two coats.
- After application , Putty should be waited between coats or before topcoat for Putty application to reach its recommended dryness.
- After application , tools should be cleaned with water.

APPLICATION DETAILS:

- Spring Exterior Acrylic Putty should be completely mixed so that it is homogenous.
- Do not apply below 5 C.

CAUTION:

- Avoid getting eye and skin contact. In case wash with plenty of water.
- Preserve in a tightly closed container.
- Keep above the reach of children
- Do not dump into sewer system.

STORAGE:

Keep at a cool and clean place away from sun light. It can be stored unopened 1 year at room temperature.

PACKAGING:

25kg, 5kg ,1 kg PE Bucket