



DESCRIPTION:Acrylic copolymer resin based, matt, water based, finish interior wall paint.

CHARACTERISTIC:

- Healthy and environmental friendly
- Easily applicable and leaves no remainings.
- High covering ability.
- Matt outward looking , colourfast for years

APPLICATION SURFACES:

Can be applied on a wide range of interior old painted surface such as concrete , plaster , wall paints , glass textile etc.

TECHNICAL INFORMATION:

Consumption: Single coat: 12- 14 (m²/ lt)

Thinner: Water

Thinning Ratio: %10- 15

Drying: Touch dry: after 15-20 min, Dust repulsive: after 1 hour, Hard dry: after 24 hours

Viscosity: 125 KU ± 10 (23 ° C)

pH: 8 – 8,5

Density: 1,62 ± 0,02 (gr / cm³)

SURFACE PREPARATION:

- The surface should be free from all kind of dust . Loose and old paintings should be scraped and surface should be dry.
- Hollows and cracks should be filled with Spring Interior Acrylic Putty in case of necessity.
- On the surfaces to be painted should be obtained by applying Spring Izolac. Old and synthetic painted surfaces should be obtained by applying Spring Universal Primer. On the surfaces which has been puttied should be obtained by applying Spring Putty Primer.

APPLICATION:

- Should be thinned 10-15% with clean water and applied with roller , brush or spraying in two coats.
- Leave minimum 2 hours between coats depending on weather conditions.
- After application , tools should be cleaned with water.

APPLICATION DETAILS:

- On new painted surfaces , make sure that surface has waited about 28 days before application.
- Material should be completely mixed so that it is homogenous.
- Do not apply below 5 C.
- Gloss and glasslike surface should be rubbed before application to obtain better adhesive and a healthy surface .

CAUTION:

- Avoid getting eye and skin contact. In case wash with plenty of water.
- Preserve in a tightly closed container.
- Keep above the reach of children. .
- Do not dump into sewer system.

STORAGE:

Keep at a cool and clean place away from sun light. It can be stored unopened 1 year at room temperature.

PACKAGING:

20kg-10kg-4kg-1kg

QUALITY CERTIFICATE

Turkish Standart TSE 5808