

SPRING BRUT BETON PRIMER

DESCRIPTION: Concrete Primer is based pure acrylic

CHARACTERISTIC: Using on the exposed concrete walls, column, and insulation system to increasing adhesion force.

APPLICATION SURFACES:

Can be applied on surfaces such as concrete, concrete finishes, column, and insulation system.

TECHNICAL INFORMATION:

Structure: Pure acrylic

Consumption: 200-250 gr/ m²

Thinning Ratio: should be diluted % 10 - % 25 with water

Application tools: Roller or brush.

Drying: Touch dry: after 15 - 20 minutes; Dust repulsive; 1 hour; Hard dry; after 24 hours

Viscosity: 110 KU ±10 (23 ° C)

pH: 8- 8,5

Density: 1,5 ± 0,05 (g / cm³)

SURFACE PREPARATION:

- All surfaces must be clean, dry and free from loose or peeling paint, grease, dirt, dust, oil
- Spring Exposed Concrete Primer can be applied after cracks has been repaired with recommended Primer.

APPLICATION DETAILS:

-It is recommended not to apply under (+) 5 C and rainy conditions

CAUTION:

Avoid getting eye and skin contact. In case wash with plenty of water.

Preserve in a tightly closed container.

Keep above the reach of children

Do not dump into sewer system.

STORAGE:

Keep at a cool and clean place away from sun light. It can be stored unopened 1 year at room temperature.

PACKAGING:

15 Kg – 12 kg